Portable battery-powered DDA for High Resolution NDT inspections

Dereo HR

XRIS

Dereo HR 1506



APPLICATIONS

Makes possible DR inspection in hard-to-reach areas :

- Small bore pipe and spool welds
- Small diameter Ti and Al pipe welds
- E-beam welds

- Civil and military aircraft NDE
- Restauration & conservations
- Welding training centers, universities, ...



KEY FEATURES

14452A	





Easy and quick set-up	Generates X-ray pictures anywhere : use the Dereo HR in a shielded cabinet or take it out at any time to use the Dereo HR as the most portable tool on site.
	Ultra light DDA (Dereo HR : 1 kg, only). Its compactness will definitely grant a high level of robustness of your Dereo UP on the field. Battery powered.
Image quality	Dynamic DDA. Immediate image after couple of seconds. Very user-friendly Maestro software. Post-processing. DICONDE format for universal file exchange. Easy archiving & reporting.
Unique	Optimized distance from the 3 sides, in order to reduce the dead area, to cover even more applications. With GemX X-ray generators, change kV and mA during. X-ray shot and adjust the image. « You just can't fail your x-ray shot ! » Automatic averaging. Dereo HR (49 μm) complies with ISO 17636-2 : - Class B for thickness higher than 1.5 mm. - Class A for thickness higher than 0.1 mm.
	calibration process and fantastic contrast resolution better than 1% (EN 462-1).
Power	Battery powered thanks to X-RIS' GUC.

Dereo HR SPECIFICATION

CERS Geno 18 206	MODEL	ACTIVE AREA (cm)	PIXEL SIZE (μm)	GREY LEVEL (bit)	FRAME RATE (fps)	EXTERNAL DIMENSIONS (mm) without bumpers	WEIGHT (kg) battery included	WIRELESS
	Dereo HR 1506	15 x 06	49	14	9	80 x 230 x 26.5	1	Yes

Unique : let us know your application and X-RIS will select the right scintillator for you.

Maestro SOFTWARE

- Software interfaces developed by and with field users
- Maestro Touch for touchpads and Maestro for laptops
- Very intuitive software interfaces. Access to all key tools of Maestro Touch with your thumbs and with one click mouse on Maestro
- Zoom in / out, screen adjustment, rotation, horizontal and vertical flip, cropping, ...
- Access to the LUT (look-up-table)
- Black and white reversal
- Annotations
- ACUITY Filter
- Real time magnifier
- Real time filters (ACUITY, Defect, Contrast, Edge, Noise reduction, ...)
- Smart measurement tools
- NDT Tools for normative inspections
- Bad pixels map
- DICONDE
- Compliant with all major NDT standards (ISO 17636, ASTM-E 2698, E2736, E2737, E2597, Safran PR5250, Airbus AITM 6-7007 and Boeing BSS-7044
- Wall thickness measurement
- Control of many X-ray generator brands and models
- Any language available upon request
- * X-RIS is open to discuss the development of new software tools

Dereo HR ACCESSORIES

X-RIS makes your job easy and supplies :

- Carrying case and backpack
- Touchpads and laptops
- GemX portable battery powered X-ray generators









Rue d'Abhooz, 25 4040 HERSTAL - BELGIUM +3243670792 | info@xris.eu 1450 Firestone Pkwy Unit A AKRON, OH 44301 - USA +18772010243 | <u>info@xris-ndt.com</u>